

Versatile and compact self-service

UX700



The Verifone UX700 is a full-featured, robust all-in-one unattended payment device utilizing the flexibility of Android OS. This versatile self-service solution provides secure and reliable transactions for vending machines, public transportation and other unattended high-transaction volume environments. Easily accept any payment type, anywhere, including mobile wallets and Advanced Payment Methods.

- Beautifully designed small footprint allows for a variety of use cases
- Designed to easily integrate into existing environments and compatible with many POS host protocols
- Weatherproof enclosure provides top level protection against dust, liquids and other harmful substances, withstanding IP65
- Tamper resistant design features anti vandalism enclosure that can withstand an impact of up to five Joules
- Powerful and secure OS - Verifone's secure version based on Android 10.x
- PCI 6.x approved
- Utilizes the power of Verifone Cloud Services for customization and estate management

Display	5" Color LCD Capacitive Multi-touch Screen LED Backlight Brightness: 800 Nits Resolution 720 x 1280 HD	Operating System	Verifone Secure OS, Engage VOS3 VAOS Based on Android 13
Multi-media	Buzzer Head-set Jack Microphone Speaker Video & Audio Playback	Processor	ARM Cortex A53, Quad Core, 2.0 GHz
User Interface	Haptic Touchscreen PIN Entry Verifone Navigator	Security	PCI 6.x Approved
Camera Barcode Scanner	Barcode + OCR + QR Decode Front 2 MP Fixed Focus Front 5 MP Fixed Focus	Connections	2 RS232 3 USB Type-A Extend Connector LAN 10/100 Base-T Multi Drop Bus USB Type-B
Card Readers	Landed Smart Card Magstripe ISO 7810, 7811, 7813 Smart Card EMVCo Approved	Power	Low Power Modes Rating 9-43V 2.4-0.5A, 6 Pin Socket
Contactless	EMVCo Approved FeliCa MiFare Supports Advanced Payment Methods Supports Major NFC/Contactless Schemes	Physical	70mm (55mm front projection) L x 107mm W x 146mm H Weight 575g Cut out 87mm x 109mm EVA SDM Compliant Weight 565g
Connectivity	2G + 3G + 4G CAT 4 Bluetooth® v5.0 Geolocation WiFi 2.4GHz + 5GHz 802.11 a/b/g/n/ac Optional UWB	Environmental	IK08 IP65 Operating Temperature: -30° to 70° C (-22° to 158° F) Storage Temperature: -30° to 80° C (-22° to 176° F) Relative Humidity: 5% to 90%, Non-condensing
Memory	2GB RAM + 32GB Flash	Other Standard Features	eSIM, SIM/SAM slot, x2 SAM slots Real-time Clock